



Rockmills Steel Products ©

(516) 829-8555

Info@rockmillsboilers.com

Over 50 years of excellence

(718) 366-8300

Specifications



Series
Horse Power:
Efficiency

MP-90SL
90 H.P.
Up to 85%

Gross Output

Steam	12555	SQ.FT
Steam	3012.8	MBH
Steam (per hr from & at 212 Deg F)	3105	LBS

Net Rating

SQ.Ft of Steam	10044	SQ.FT
MBH of Steam	2410.2	MBH

Firing Rate

Light Oil (140000 BTU/Gal)	26.2	GPH
Heavy Oil (150000 BTU GAL)	24.5	GPH
GAS	3674.1	MBH

General Information

Heating Surface	450	SQ.FT
Furnace Volume	55.304	CU. FT
Safety Valve Relieving Capacity - Required Steam (Min)	3600	LB/HR
Steam Outlet Pipe Size	8	IN
Dry Boiler Weight (Approximate)	12,753	LB
Operating Weight (Approximate)	20,134	LB



Rockmills Steel Products ©

(516) 829-8555

Info@rockmillsboilers.com

Over 50 years of excellence
(718) 366-8300

Dimensions




Series MP-4

Horse Power:
Efficiency

MP-90SL

90 H.P.
Up to 85%



** As per ASME code all boilers with a diameter greater than 60" will be equipped with 12"x16" manhole

Dimensions

A	Overall Length	15-7 7/8	FT-IN.
B	Overall Height	73.5	IN.
C	Shell Diameter (Over jacket 2" thick)	58	IN.
D	Shell Length	13-4 5/8	FT-IN.
E	Furnace Diameter	27	IN.
F	Furnace Length	135.625	IN.
G	Height-Centerline of Furnace	29.0625	IN.
H	Normal Water Line	57.5625	IN.
J	Depth-Front Reversing Chamber	8.75	IN.
K	Height-Front Rev. Chamber Top	55.1875	IN.
L	Height-Front Rev. Chamber Bottom	32.6875	IN.
M	Depth-Rear Combustion Chamber	18	IN.
N	Vent Outlet Diameter	16	IN.
P	Depth-Smoke Box	17.75	IN.
Q	Height-Smoke hood Top	40.4375	IN.
R	Height-Smoke hood Bottom	46.5625	IN.
S	Tube Pull	13-4 5/8	FT-IN.
U	Saddle Width	8	IN.
V	Saddle Length	42	IN.
W	Position-Front Saddle	8	IN.
X	Position-Rear Saddle	21	IN.
Y	Centerline of Access Door	29.5	IN.
Z	Manhole	12 x 16	IN.
	Handhole	3 x 4	IN.